

IN THE CLAIMS:

Please cancel claims 16 and 29 without prejudice.

Please withdraw from consideration claims 21-28.

Please amend claims 1, 2, 11, 12, 17, 20, and 30 as follows:

1. (currently amended) An apparatus for partitioning moving picture data comprising:

a first quantizing unit for first-quantizing a received video signal and outputting a first-quantized signal; and

a second quantizing unit for second-quantizing the first-quantized signal to produce a re-quantized signal, and partitioning the first-quantized signal into a preceding part generated from the re-quantized signal, and a succeeding part [[.]] in which a difference signal is generated from the first-quantized signal and the preceding part;

a first variable length coding unit for coding the re-quantized signal; and

a second variable length coding unit for coding the difference signal.

2. (currently amended) An apparatus for partitioning moving picture data comprising:

a first quantizing unit for first-quantizing a received video signal and outputting a first-quantized signal; the first quantizing unit comprising a first quantizer for quantizing the received video signal, and

a second quantizing unit for second-quantizing the first-quantized signal and partitioning the first-quantized signal into a preceding part and a succeeding part The apparatus of claim 1, wherein the second quantizing unit comprises:

a second quantizer for re-quantizing the first-quantized signal to generate an output signal;

a first variable length coder (VLC) for variable-length coding the output signal generated by the second quantizer;

a second inverse-quantizer for inverse-quantizing the output signal generated by the second quantizer;

a ~~third~~ combiner for performing subtraction operation of output signals generated by ~~a~~ the first ~~inverse~~-quantizer and the second inverse quantizer;

a second VLC for variable-length coding output signals generated by the third combiner and the second quantizer; and

a data partitioner for outputting output signals generated by the second VLC and the first VLC.

3. (original) The apparatus of claim 1, wherein the preceding part and the succeeding part comprise at least one frequency component.

4. (original) The apparatus of claim 2, wherein the second quantizer outputs an even-approximated coefficient as the preceding part by having a quantization interval set to a predetermined value.

5. (original) The apparatus of claim 2, wherein an output signal of the third combiner is an odd-remainder coefficient as the succeeding part equal to a predetermined value.

6. (original) The apparatus of claim 5, wherein the odd-remainder coefficient comprises code information when the odd-remainder coefficient is equal to a first value and a pertinent even-approximated coefficient is not equal to a second value.

7. (original) The apparatus of claim 6, wherein the first value is approximately 1.

8. (original) The apparatus of claim 6, wherein the second value is approximately 0.

9. (original) The apparatus of claim 5, wherein the odd-remainder coefficient as the succeeding part is equal to approximately 0.

10. (original) The apparatus of claim 5, wherein the odd-remainder coefficient as the succeeding part is equal to approximately 1.

11. (currently amended) An apparatus for partitioning moving picture data comprising:

a coding unit for outputting a stream comprising a DCT coefficient divided into an even-approximated coefficient and an odd-remainder coefficient by first-quantizing a received video and second-quantizing a first-quantized signal ~~received video signal~~; and

a decoding unit for obtaining a first-quantized signal by performing inverse-quantization about the stream generated by the coding unit and obtaining a restored video signal by performing inverse-quantization about the first-quantizing[.];

an inverse-quantizing unit for inverse-quantizing the re-quantized signal and calculating a difference signal based on the first-quantized signal; and

a variable-length coding unit for coding the re-quantized signal and the difference signal.

12. (currently amended) An apparatus for partitioning moving picture data comprising:

a coding unit for outputting a stream comprising a DCT coefficient divided into an even-approximated coefficient and an odd-remainder coefficient by first-quantizing a received video and second-quantizing a first-quantized signal; and

a decoding unit for obtaining a first-quantized signal by performing inverse-quantization about the stream generated by the coding unit and obtaining a restored video signal by performing inverse-quantization about the first-quantizing,

~~The apparatus of claim 11, wherein the coding unit comprises:~~

a first quantizer for outputting a first-quantized signal by first-quantizing a received video signal;

a second quantizer for outputting an even-approximated coefficient by re-quantizing the first-quantized signal;

a first VLC (variable length coder) for variable-length coding an output signal of the second quantizer;

~~an second~~ inverse-quantizer for inverse-quantizing an output signal of the second quantizer; ~~and~~

a ~~third~~ combiner for outputting an odd-remainder coefficient by performing subtraction operation of output signals of the second inverse-quantizer and the first quantizer;

a second VLC (variable length coder) for variable-length coding output signals of the ~~third~~ combiner and the second quantizer; and

a data partitioner for outputting output signals of the second VLC and the first VLC as a data-partitioned stream.

13. (currently amended) The apparatus of claim 12, wherein an output signal of the ~~third~~ combiner is an odd-remainder coefficient.

14. (original) The apparatus of claim 13, wherein the odd-remainder coefficient comprises code information when it is equal to a first value and a pertinent even-approximated coefficient is not equal to a second value.

15. (original) The apparatus of claim 12, wherein the decoding unit comprises:

a divider for dividing the data-partitioned stream into a preceding part and a succeeding part;

a first VLD (variable length decoder) for outputting an even-approximated coefficient by variable-length decoding the preceding part;

a first inverse-quantizer for inverse-quantizing an output signal of the first VLD;

a second VLD (variable length decoder) for variable-length decoding the succeeding part;

a first combiner for outputting a first-quantized signal by combining an output signal of the first inverse-quantizer with an output signal of the second VLD; and

a second inverse-quantizer for outputting a video signal by performing inverse-quantization and inverse discrete cosine transform of the first quantized signal.

16. (cancelled)

17. (currently amended) A method for partitioning moving picture data, the method comprising:

outputting a first-quantized signal by first-quantizing a received video signal;

partitioning the first-quantized signal into a preceding part and a succeeding part through a second quantization; and

outputting an output signal generated as result of the second quantization as a partitioned stream signal

~~The method of claim 16, wherein the partitioning step comprises:~~

~~re-quantizing the first-quantized signal to generate a re-quantized signal;~~

~~variable-length coding the re-quantized signal;~~

~~inverse-quantizing the re-quantized signal and calculating a difference based on the first-quantized signal; and~~

~~variable-length coding the calculated difference.~~

18. (original) The method of claim 17, wherein the re-quantized signal is an even-approximated coefficient corresponding to the preceding part.

19. (original) The method of claim 17, wherein the calculated difference is an odd-remainder coefficient corresponding to the succeeding part.

20. (currently amended) The method of claim 4617, wherein a stream is constructed by inserting a texture marker for separating the preceding part and the succeeding part.

21. (withdrawn) A method for partitioning moving picture data, the method comprising:

generating a first-quantized signal by first-decoding a received stream; and
restoring a video signal by second-decoding the first-quantized signal.

22. (withdrawn) The method of claim 21, wherein the generating comprises:
dividing the received stream into a preceding part and a succeeding part;
variable-length decoding and inverse-quantizing the preceding part;
variable-length decoding the succeeding part; and
outputting the first-quantized signal by adding the preceding part to the succeeding part.

23. (withdrawn) The method of claim 22, wherein the preceding part is an even-approximated coefficient.

24. (withdrawn) The method of claim 22, wherein the succeeding part is an odd-remainder coefficient.

25. (withdrawn) A system for partitioning moving picture data, the system comprising:

a first inverse-quantizing mechanism for generating a first-quantized signal by first-quantizing a preceding part and a succeeding part of a data-partitioned stream; and
a second inverse-quantizing mechanism for outputting a video signal by performing inverse-quantization and inverse discrete cosine transform of the first

quantized signal.

26. (withdrawn) The system of claim 25, wherein the first inverse-quantizing unit comprises:

a divider for dividing the received data-partitioned stream into a preceding and a succeeding part;

a first variable length decoder (VLD) for performing variable-length decoding of the preceding part to generate a first output signal;

a first inverse-quantizer for inverse-quantizing the first output signal of the first VLD;

a second VLD for performing variable-length decoding of the succeeding part; and

a first combiner for outputting a first-quantized signal by combining an output signal of the first inverse-quantizer with an output signal of the second VLD.

27. (withdrawn) The system of claim 26, wherein an output signal of the first VLD is an even-approximated coefficient.

28. (withdrawn) The apparatus of claim 26, wherein an output signal of the second VLD is an odd-remainder coefficient.

29. (cancelled)

30. (currently amended) A method of partitioning a streaming data, the method comprising:

quantizing the streaming data to generate a first quantized signal;

quantizing the first quantized signal to obtain an even-approximated coefficient;

obtaining an odd-remainder coefficient;

variable-length coding the even-approximated coefficient and the odd-remainder coefficient; and

outputting a data-partitioned stream based on said variable length coding.

~~The method of claim 29 further comprising:~~

partitioning the data-partitioned stream into a plurality of data streams;

variable-length coding the respective data streams;

obtaining an even-approximated coefficient and an odd-remainder coefficient
through ~~first~~ second-inverse quantization to output a restored video signal, based on a
~~second~~ first quantization[.].]

;calculating a difference signal based on the first-quantized signal; and

variable-length coding the calculated difference.